HZ FISHING JARS

TTS fishing jars feature a newly improved firing assembly engineered for consistent jarring times and extended tool life, with up to 450 hits recorded on a single jar without failure. The 2 3/8 PH6 and 2 7/8 PH6 models provide a full open ID, allowing cutting and wireline tools to pass through the jar and save valuable time on the job.

For horizontal applications, TTS HZ fishing jars offer low re-cocking force and repeatable upward or downward jarring, with impact controlled by the applied force. No pre-setting or downhole adjustments are required, helping simplify operation when it matters most.



HZ FISHING JARS					
Tool Sizes	**2.38 TTSC**	**3.13 PH6**	**3.13 REG**	**3.50 IF**	**3.75 PH6**
Tool Size (OD)	**2.38”**	**3.13”**	**3.13”**	**3.50”**	**3.75”**
Tool Size (ID)	**0.94”**	**1.50”**	**0.94”**	**1.625”**	**1.94”**
Total Length*	**7.38’**	**7.38’**	**7.38’**	**7.38’**	**7.73’**
Max Pull Load (lbs)	**58,000**	**45,000**	**58,000**	**35,000**	**40,000**
Lift Load After Jarring (lbs)	**234,428**	**199,295**	**234,428**	**213,000**	**218,400**

Overall tool lengths are in the closed position.*

THRU TUBING SOLUTIONS